

FHS Filter Specification

Document No:
2-01-100-0

Filter Specifications

CONSTRUCTION

PLEATED FILTER MEDIA, FOR MAXIMUM DIRT CAPACITY AND MINIMUM FLOW RESTRICTION.
SEAMS ARE WELDED AND THE ENDS ARE BONDED USING A HIGH PERFORMANCE EPOXY ADHESIVE.

MATERIALS (UNLESS SPECIFIED)

FILTER MEDIA : CLEANABLE, WOVEN STAINLESS STEEL MESH

ENDS : BLACK ANODISED ALUMINIUM ALLOY 2014.
STAINLESS STEEL OR TITANIUM AVAILABLE ON REQUEST.

TEMPERATURE RATINGS

FILTERS : -40°C TO +180°C

SEALS (VITON) : -25°C TO +250°C

APPLICATIONS

GEARBOX OIL, POWER STEERING, HYDRAULICS, ENGINE OIL,
WATER COOLING, FUEL PRE-FILTER, FUEL PRESSURE LINE,
AIR BREATHERS, FLUSHING/FILLING RIGS

FOR OPTIMUM SIZE AND FILTER RATING GUIDANCE PLEASE CONTACT FHS MOTOR RACING LTD.



656 Ajax Avenue, Slough, Berkshire, SL1 4BH

Tel: +44 (0)1753 513080 Fax: +44 (0)1753 513099

www.fhsracing.co.uk e-mail: info@fhsracing.co.uk